

# SRS-6s

## Meet the SRS-6s.



Introducing the Somero SRS-6s Laser Screed® machine - which seamlessly retains the exceptional benefits of its predecessor, the SRS-4, while introducing enhancements that redefine maneuverability and a 12' head that increases production.

Unlocking unprecedented manueverability, the SRS-6s features Head Shift: a head with capability to move left to right with an impressive 24" shifting range—12" each way from the center. This feature empowers operators with unmatched versatility, facilitating precise screeding around obstacles with ease. Bid farewell to frequent stops for turning and maneuvering—with advanced steering capability in screed mode. This feature enables seamless adjustments on the go, significantly boosting productivity.

Contact us today at Sales@Somero.com / 1-239-210-6519 or visit SOMERO.COM to learn more!

#### FEATURES/BENEFITS:

- Head Shift means increased flexibility in positioning; utilization of proportional hydraulics allows for precise adjustments during operation.
- 12' head that increases production.
- Powerful 25hp Kubota diesel engine with Tier 4 Final compliant emissions; no D.E.F. or regeneration required
- 4-wheel drive for incredible traction in any subgrade condition.
- Manual head rotation feature means no head removal for easy transportion and accessing projects.
- Tilt assist for easy cleaning of the machine head.
- Operator selectable self centering steering includes 2-wheel, 4-wheel, and crab modes for seamless maneuverability while driving sideways, eliminating the need to toggle between modes for repositioning.
- Utilizes the Somero® signature features such as Quick GradeSet System® for fast 1-person set up, QuickPass, Soft Landing, Column Block protection, Head Self-Level-System, and more to maximize efficiency and quality with every pass
- Compatible with Somero ® 3-D Profiler System ®
- 3 NEW drive modes for unparalled maneuverability
- Effortless movement with the ability to turn and maneuver in screed mode, improving overall efficiency and reducing repositioning time.

### SPECIFICATIONS:

NOMINAL WEIGHT	5,150 lbs / 2,336 kg (Without Options)
FULLY LOADED WEIGHT	5,920 lbs / 2,676 kg (With All Options)
WIDTH	6'2" / 1.8 m (Outside of tires)
HEIGHT	6'4" / 1.9 m
LENGTH	15' 4" / 4.67 m (Drive mode, boom retracted)
BOOM LENGTH	18' / 5.4 m
SCREED HEAD WIDTH	
STANDARD	13'3" /4.0 m
VIBRATOR WIDTH	12' / 3.6 m
ENGINE	Kubota V1505, 24.8 Hp Diesel







#### **OPTIONS:**

- Tool Box/ On board storage

- Spare Tire

- Pressure Washer Kit

- Spray System

- Operator Platform

- Two 16 gallon tanks for fluid storage

- Spare Parts Kits